



## **B1 SERIES**B1161/B1181/B1241

Three new models with the power and versatility you need to get your jobs done quickly, safely, and efficiently.







B1181 KUBOT

## The right combination of power and versatility for every job

Designed with your needs in mind, the new B1 Series offers three model variations with different combinations of power and features to let you perform any job with maximum efficiency and economy. The new B1 Series features powerful and dependable 16-, 18-, or 24-hp engines with high torque, cleaner emissions, and low noise and vibration. All three models are also ready for the road, letting you move safely and quickly from site to site.

B1161/B1181 B1241

180521\_B1\_UK \$1.Indd 4 12/07/2018 16:38

# The New Blands B

The new B1 Series' clean, sophisticated design is both luxurious and functional, with a sleek slanted bonnet for an improved view, combination lamps that serve to both illuminate dark sites and for indication, powerful multi-reflective headlamps to let you work efficiently and travel safely, and a streamlined, easy-to-clean front grill.

#### **Slanted Bonnet**

Offering a clear view of the front, the slanted bonnet improves visibility during front loader operations.

#### **Combination Lamps**

Bright and powerful, the new B1 Series' combination lamps provide extra illumination to the sides on dark sites and also serve as indicators.

#### Headlamps

These multi-reflective headlamps shine brighter and further, letting you work efficiently and travel safely.

#### Front Grill

Designed to match the slanted bonnet, the new B1 Series' streamlined front grill is also easy to clean.



180521\_B1\_UK S1.lndd 5 12/07/2018 16:38





#### Rear Mounted ROPS/Malfunction Prevention Screen

Standard on all of the new B1 Series models, this screen protects the driver from performing potentially dangerous tasks.



#### **Mirrors**

The convenient mirrors let you keep your eyes safely on the action ahead while closely monitoring the action behind.



#### Handgrip

For easier entry and exit, all new B1 Series models feature a handgrip on the left side.



#### Open Bonnet System

A redesigned bonnet latching system provides greater safety when opening the bonnet for maintenance.



#### **Engine Start Safety System**

A three-tier safety system. Ensures that the engine doesn't start until it is safe to do so.

- 1) seat occupied,
- 2) PTO off,
- 3) clutch pedal pressed



#### **Parking Brake**

A buzzer sounds if the operator leaves the seat without setting the parking brake.



#### Auxiliary Step (B1241 only)

The B1241 model offers a step on the left side for easier and safer entry and exit.



#### **Engine Key Stop**

A 4-position (preheat/on/off/ start) key-operated switch operates a solenoid to shut off the engine.

180521\_B1\_UK S1.Indd 6 12/07/2018 16:38

## Enhanced Performance

No matter what the task, there's a new B1 Series tractor ready to take it on. Choose from three models, each with a unique set of features that is tailored to specific tasks, such as the B1181's Mid-PTO for mowing tasks. Each also offers a reliable, Stage 5 compliant engine with the right amount of output—16, 18, and 24 PS—to ensure optimum performance efficiency and cost effectiveness.



#### **Diesel Engine**

Every B1 Series model is built around a rugged and reliable Kubota E-TVCS (three-vortex combustion system) engine that provides increased power, high torque, cleaner emissions, and low noise and vibration. All engines are equipped with a large-capacity 480W alternator that reliably provides electrical power even on cold winter days.





180521\_B1\_UK S1.lndd 7 12/07/2018 16:38





#### Power Steering (B1181/B1241)

Highly efficient power steering provides easier maneuverability and more responsive control, particularly in soft ground. A vibration damping mechanism reduces fatigue and increases comfort when working long hours.



#### High-Capacity Radiator

The new B1 Series' high capacity radiator keeps the engine cool and operating at maximum efficiency even on the hottest summer days.



#### **Bevel-Gear 4WD**

When the going gets tough, the new B1 Series keeps going, thanks to a bevelgear 4WD that provides power to all four wheels whenever extra traction is required. Bevel-gear 4WD also provides a higher ground clearance as well as the tightest turning radius in the new B1 Series' class.



#### 3-Point Hitch

All new B1 Series models feature Kubota's Category I 3-point hitch for use with rear implements.

#### **Durable Wet Disc Brakes**

With just a light touch of the brake pedal, Kubota's wet disc brakes provide even and powerful braking force. You'll stop faster with greater control, thereby ensuring optimum safety.

180521\_B1\_UK S1.lndd 8 12/07/2018 16:38

## Enhanced Comfort

Comfort is important, especially when you're working long hours in the field. The new B1 Series ensures that you'll remain comfortable all day long, offering a host of ergonomic features that include a full rubber operator platform, cup holder, and hand grips.

#### Semi-Flat, Full Rubber Covered Deck

Every new B1 Series model features a deck fully covered in durable rubber to dampen vibrations and provide extra comfort for your feet.





#### Lever Guides (B1181 and B1241)

Large angled lever guides ensure quicker lever recognition and more accurate shifting. All levers are conveniently positioned for fast access.

#### **Useful Cup Holder**

A convenient cup holder keeps your beverage tumbler or travel mug within easy reach, allowing you to quickly quench your thirst.





180521\_B1\_UK S1.lndd 9 12/07/2018 16:38



### Enhanced Maintenance



#### **Backlit Instrument Panel**

A redesigned instrument panel helps you keep track of vital tractor functions. The panel backlight activates when the headlamps are turned on.



#### **Air Cleaner**

Located under the bonnet for quick and easy access, the single-element air cleaner can be quickly changed. A clean air filter improves gas mileage and performance, reduces emissions.

180521\_B1\_UK \$1.lndd 10 12/07/2018 16:38



180521\_B1\_UK \$1.Indd 11 12/07/2018 16:38

### Tractor Implements

#### A versatile array of implements to get the job done right

#### Mid-PTO (B1181)

The B1181 features a mid-mount mower PTO shaft drive that provides superior operational performance and durability as well as quick and easy maintenance. Attach Kubota's 48" mid-mount mower deck, and enjoy superb cutting performance even in long or wet grass.



#### **LOADER SPECIFICATIONS**

Maximum lift height (to bucket pivot pin)     mm     1921       Clearance w/bucket dumped     mm     1445       Reach at maximum lift height (dumping reach)     mm     815       Maximum dump angle     degrees     44       Bucket roll-back angle     degrees     24       Digging depth at bucket levelled     mm     110       Overall height in carrying position     mm     1070       Bucket width     mm     1067       Lift capacity (bucket pivot pin)     kg     302       Lift capacity (500 mm forward)     kg     208       Breakout force (bucket pivot pin)     N     6546
Reach at maximum lift height (dumping reach)     mm     815       Maximum dump angle     degrees     44       Bucket roll-back angle     degrees     24       Digging depth at bucket levelled     mm     110       Overall height in carrying position     mm     1070       Bucket width     mm     1067       Lift capacity (bucket pivot pin)     kg     302       Lift capacity (500 mm forward)     kg     208
Maximum dump angle         degrees         44           Bucket roll-back angle         degrees         24           Digging depth at bucket levelled         mm         110           Overall height in carrying position         mm         1070           Bucket width         mm         1067           Lift capacity (bucket pivot pin)         kg         302           Lift capacity (500 mm forward)         kg         208
Bucket roll-back angle degrees 24  Digging depth at bucket levelled mm 110  Overall height in carrying position mm 1070  Bucket width mm 1067  Lift capacity (bucket pivot pin) kg 302  Lift capacity (500 mm forward) kg 208
Digging depth at bucket levelled mm 110  Overall height in carrying position mm 1070  Bucket width mm 1067  Lift capacity (bucket pivot pin) kg 302  Lift capacity (500 mm forward) kg 208
Overall height in carrying position mm 1070  Bucket width mm 1067  Lift capacity (bucket pivot pin) kg 302  Lift capacity (500 mm forward) kg 208
Bucket width mm 1067 Lift capacity (bucket pivot pin) kg 302 Lift capacity (500 mm forward) kg 208
Lift capacity (bucket pivot pin) kg 302 Lift capacity (500 mm forward) kg 208
Lift capacity (500 mm forward) kg 208
Brookout force (bucket pivet pip) N 6546
Breakout force (bucket pivot piri)
Breakout force (500 mm forward) N 4508
Raising time to full height w/o load sec. 3.6
Lowering time w/o load sec. 2.7
Bucket dumping time sec. 1.5
Bucket rollback time sec. 2.5



#### LA213 Front Loader

### Take on those tough loading jobs with ease and efficiency

The new B1 Series' front loader is ready for the toughest front loading jobs, offering a 42" loader bucket, braceless frame, protected hydraulics, a tractor-integrated single-lever joystick, quick attach/detach system, heavy-duty mounting frame, curved boom, and optional front guard.





180521\_B1\_UK S1.lndd 12 12/07/2018 16:38

#### **Specifications**

Model			B1161D-EC	B1181DT-EC	B1241D-EC
Road approval			Approved (EC homologated model)		
			w/o Mid PTO	w/ Mid PTO	w/o Mid PTO
Engine					
Туре				E-TVCS, liquid, 3-cylinder diesel	
Make, Model			Kubota D722	Kubota D782	Kubota D1105
Engine power SA	AE aross	kW (PS)	11.8 (16)	13.2 (18)	17.9 (24.0)
Engine power ECE-R24		kW (PS)	10.3 (14)	11.9 (16)	15.8 (21.5)
PTO power (*1)		kW (PS)	9.1 (12.4)	10.3 (14.0)	14.3 (19.4)
No. of cylinders		(. 0)	(.=)	3	( ,
Bore & stroke		mm	67 × 68	67 × 73.6	78 × 78.4
Total displacement		cm <sup>3</sup>	719	778	1123
Rated speed		rpm	2900	3000	2600
Muffler and exhaust pipe		ipini	2300	Fully enclosed	2000
			Single		Double
Air cleaner		P		14	26
Fuel tank capacit	ıy	ε		14	20
Driving method				OWD A AWD	
Driving method			2WD ⇔ 4WD		FC/D2
Transmission spo		Luna /la		=6/R2	F9/R3
Max. travelling sp	peea	km/h	17.5	19.3	18.9
Differential lock				STD	
Brake type			Wet mulch disk		
Steering	Steering		Manual	Power ste	eering
PTO	_		_	T	L.
Rear PTO	Type			Transmission driven with one way clutch	
	Speed	rpm	540	540/1000	540
Mid PTO (*2)	Speed	rpm	N/A	2500	N/A
Hydraulic system					
Pump capacity		ℓ/min		14.1	16.9
Lift control type			8	Select	Select (Q.I.V)
Lift capacity	Lift capacity Link end kg		540		615
3-point hitch			category I		
Dimensions				<u> </u>	
Overall length		mm	2	2360	2410
Overall width (min. tread)		mm	938		990
Overall height		mm	2217-2293 (ROPS)		2013-2350 (ROPS)
Wheelbase		mm	1270		1563
Tread	Front	mm	767-867		797-815
11000	Rear	mm	760-1006		760-1006
Ground clearanc		mm	240-316		267-313
		m	1.8		207-313
			5-12		
Standard tyre			8-16		6-12
	Rear: Farm				9.5-16
	Front: Turf		20 x 8.00-10 212/80D-15		
	Rear: Tur				
Weight		kg	639-674	635-670	732-787
Comfort Headlamp			Multi	reflective with halogen valve (EC appro	oved)
Operator's deck		Semi-flat, full rubber covered deck  Full flat, full rubber covere			
Backlit instrument panel				STD	
Cup holder			STD		
Operator's noise level (*3) dBA			82.8 84.9		
Other Features		UD/ (	02.0		
EC approved BOPS				STD	
EC approved back mirror kit			STD		
Rear work-light kit				OPT	
EC approved drawbar kit				STD	
EC approved from	nt hitch kit		OPT (need fot	public road driving)	STD

The company reserves the right to change the above specifications without notice.  $^{(1)}$  Manufacturer's estimates.

©2018 Kubota Corporation



#### **KUBOTA (U.K.) LIMITED**

Dormer Road Thame, Oxfordshire, OX9 3UN. Phone (01844) 268000

www.kubota.co.uk









Cat.No.4347-00-UK Printed in the UK, D.REX, '18-JULY.

<sup>(\*2)</sup> Mower deck can be attached to the tractor only with turf tyre 20x800-10, 212/820D-15.
(\*3) B1161EC/B1181EC/B1241EC: Measures according to Regulation (EU) 1322/2014 XIII.